

Intumescent Letterbox



FRAMEMASTER INTUMESCENT LETTERBOX

1 hour intumescent letterplates

Letterplate conforms to the requirement of BS/EN13724:2002

Satin Silver
White
Black

180 degree opening on both sides means that flaps cannot be snapped easily when opening as the flap will be stopped by the face of the door or window profile

Internal water seal prevents water getting into the door or panel

water channels carry rain water away from the post and harmlessly down the sides of the letterplate

180 degree opening on both sides

NEW CHROME FINISH AVAILABLE

REAL PVD Available

Brushes face the outside of the door for 3 very important reasons;

1. Makes for better draught proofing
2. It is easier for the postal service to post letters
3. It stops vandals placing unwanted items i.e. fireworks, dog litter in the letterplate cavity.

Only post gets through our letterplate

Galvanised steel frame means the brushes won't rust.

Blind bolts to the exterior prevents the outer frame being unscrewed from the door from the outside.

Burglars can't unscrew our letterplate

Ultra flexible springs means the letterplate will withstand thousands of openings without breaking

Scratch resistant surface means that attempts to deface the product using nails, or knives are virtually invisible

Scratches are hidden on our letterplate

Aperture Required

FIXING DETAILS

Fit the letterplate with the brushes facing to the outside. Fit the inner half of the letterplate using 4 of the screws. Fit the outer half using the 4 washers and the 4 remaining screws.

	Overall size	Postal Dimensions		Black Scratch Resistant Frame						
		Height	Length	Gold Flap	White Flap	Black Flap	Silver Flap	Chrome Flap	PVD Gold Flap	PVD Chrome Flap
40 - 80mm	300mm (12")	42mm	248mm	FMB1248G	FMB1248W	FMB1248B	FMB1248S	FMB1248C	FMB1248PVDG	FMB1248PVDC

SECURITY COWL

Obstructs view, prevents manipulation of locks and inhibits vandalism.

